

# caroma®

## Cosmo

**Vitreous China  
Wall Basin**

Nominal Size 500mm x 440mm

CI/SfB	(74.2)	g3
Date	December 2009	

Supersedes all previous issues

# 1.06.1



(Tapware and Pedestal shown are not included)  
Shown with chrome waste (supplied as standard mid 2010)

# Cosmo

## Vitreous China Wall Basin

Basin Size: 500mm x 440mm (nominal)

## Vitreous China Pedestal

## Vitreous China Shroud



Contemporary style doesn't have to mean edges and angles, nor does it have to cost the earth. The Caroma **Cosmo** wall basin is surprisingly economical whilst offering elegant curves and a very modern aesthetic. Due to its compact size, a wall basin has always been a practical choice. With the addition of a pedestal or shroud, it becomes a beautiful one as well. Also suitable for installation with the Modina bottle trap whose smart chrome finish balances form and function for a brilliant bathroom solution.

**Tap Holes:** Basin available in: no taphole option Code No.861505; one taphole – centre option Code No.861515; three taphole option Code No.861535.

**Waste Outlet:** The basin has been designed for the Caroma Uni-waste outlet suitable for a 40mm trap connection.

Coloured plastic flush fitting Uni plug and waste supplied. For applications where a chrome plated brass waste is required there are four suitable Uni-wastes available in the following options — Flush Fitting Plug and Waste Code No.687140, Vandal Resistant Flush Fitting Plug and Waste Code No.687141, Covered Plug and Waste Code No.687142 and Vandal Resistant Covered Plug and Waste Code No.687143.

**Pedestal:** Pedestal, Code No.639900. Accurate setout and use of recommended traps is essential for optimum installation. S-trap – 40mm standard Caroma plastic traps.

**Shroud:** Shroud, Code No.639950, completely conceals P-trap waste pipe fittings. Use D.210 fixing clip suitable with D.200 bracket option and 40mm Caroma plastic P-trap Code No.102112. **Note:** It is essential for the installation of the shroud to the basin that clearance is provided for the shroud in the plumbing setout from water inlet pipes and connections.

**Bowl Capacity:** 4 litres to overflow.

**Overflow:** Overflow available only. Designed for maximum tap flow rate of 15 litres/minute.

**Fixing:** **D.200 Basin Fixing Kit** – Supplied. Bolts directly to the finished wall.

**Colours:** White and Ivory.

**Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

