

caroma®


GEO®

Vitreous China Wall Faced
Box Rim Pan

CI/SfB	(74.2)	g3
Date	July 2008	

Supersedes all previous issues

4.02.1



Geo Back Inlet

Vitreous China Wall Faced Box Rim Pan



A geometric minimalist designed box rim wall faced pan with 575mm projection from the wall and features smooth sides and setout adjustment, suitable for general purpose applications. The Uniconnector allows for push-on trap connection with the advantage that it does not require an access panel to connect the flush pipe during S-trap installation. The combination of the straight geometric surfaces and concealed plumbing fittings with the wall face concept provides for optimum ease of cleaning and low cost maintenance enhanced by the rim design which maximises the washed area of the bowl. The **Geo** back inlet pan can be coupled with the Caroma range of concealed cisterns. The pan is suitable for domestic and commercial applications.

- Pan:** **Geo Smartflush** back inlet 4.5 litre full flush wash down pan with partial box flushing rim.
- Traps:** Universal trap for S or P-trap installations.
- Inlet:** 50mm back inlet for concealed cistern and flushvalve installation.
- Cisterns and Flushvalves:** Caroma Concealed Cistern options available – **Invisi II Under Counter/Inwall/ Induct/Inceiling Cisterns** see Section 6 (available November 2008). **Invisi Inwall/Induct/Inceiling Cisterns, Compact Under Counter Dual Flush Cistern, Slimline Induct Cistern, Schell WC Flushvalve Inwall/ Induct** see Section 6.
- Fixing:** The pan can be fixed to the floor by either bedding into mortar or using the **D.80 Concealed fixing bracket**.
- Seats:** The **Geo** seat is recommended. See Sheet 5.01 SEATS for further details.
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Top view dimensions: 425 (height), 150 (width), 575 (total height), 400 (width).

Side view dimensions: 395 (height), 185 (height), 138 (width), 235 (width), 30 (height), 90 min (height), 575 (width), 358 (height), 937 (height), 330 (height), 185 (height), 395 (height).

Front view dimensions: 400 - 420 Frame, 45 (height), 642 min. (height), 582 (height), 937 (height), 358 (height), 210 (width), 110 (width), 55 (height), 30 (height), 575 (width), 30 (height), 330 (height), 185 (height), 395 (height).

Labels: Pan foot level, D.80 Concealed Fixing Bracket, Access plate and buttons, Invisi II cistern, Integrated flush pipe support, Recommended 90mm setout, centre of back inlet, Integrated isolating valve supplied.

Geo Pan	Code No.
Standard back inlet	
4.5 litre	824001
Geo Seat	301297

To achieve 4 star water efficiency rating, this pan should be matched with:

Invisi II Smartflush 4 star 4.5/3 litre Cistern	237001
(available November 2008)	

D.80 Concealed Fixing Bracket

Note: All height dimensions to underside of pan, make allowance for bedding.

Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.

Bracket fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with the D.80 Fixing Brackets supplied.