

caroma®

Opal 2000


Vitreous China 4.5/3 litre Dual Flush
Wall Faced Close-Coupled Toilet Suite



CI/SfB	(74.1)	g3
Date	July 2008	

Supersedes all previous issues

3.23.3





A fully integrated wall faced close-coupled Smartflush toilet suite featuring a compact 4.5/3 litre dual flush cistern with low profile chrome plated push buttons and a universal connection system for varying pan setouts. The suite uses Caroma Smartflush technology to deliver the latest water-saving technology in sanitaryware products and has been designed to provide low cost maintenance by incorporating easy to clean rounded surfaces combined with the advantages of a wall faced pan and a back inlet 1/2" B.S.P. water connection which completely conceals both the inlet and stop valve and outlet connections. The Uni-Connector pan connecting system allows for setout adjustable from 80mm to 180mm with a recommended setout of 140mm providing installation versatility for both new and renovation applications. A 50mm DWV vent coupling option is available that can be simply fitted to the Uni-Connector which is ideal for use on renovation projects with existing pan venting systems. The suite has been developed to meet the needs of a modern Australian industry to provide the designer with the ultimate water-saving technology vitreous china toilet suite. For an update on Smartflush refer to www.smartinnovation.com.au

The back inlet cistern is fitted with an ultra quiet fast fill inlet valve as standard.

- Pan:** Opal 2000 Smartflush 4.5 litre full flush washdown pan with open flushing rim.
- Traps:** Universal trap for S or P-trap installations. 50mm vent option available.
- Cisterns:** Opal 2000 Smartflush Cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Standard back inlet.
- Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy use commercial areas. Code No.750109.
- Cistern inlet stop valve and inlet copper connection is concealed within the cistern and is included.
- Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.**

- Fixing:** The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.
- Seats:** The Avalon Commercial toilet seat is provided as standard with the Opal 2000 suite. A quality solid section compression moulded toilet seat fitted with buffers and chrome hinges.
- Colours:** White and Ivory.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

