

caroma®


CI/SfB	(74.1)	g3
Date	July 2008	

Supersedes all previous issues

Opal II Easy Height

3.23.2

Vitreous China 4.5/3 litre Dual Flush
Wall Faced Box Rim Close-Coupled Toilet Suite



Opal II Easy Height

Vitreous China 4.5/3 litre Dual Flush Wall Faced Box Rim Close-Coupled Toilet Suite



A modern close coupled 4.5/3 litre dual flush toilet suite with clean simple lines the fully integrated wall faced toilet suite featuring a raised height seat, smooth rounded surfaces and concealed plumbing fittings provides for optimum appearance and ease of cleaning. Ideal for aged care applications where a raised height seat offers the advantage of easier use for persons with restricted movement. The **Opal II Easy Height Smartflush** matched suite uses Caroma Smartflush technology to deliver the latest water saving technology in sanitaryware products. A matching soft close seat is provided as standard. The Uni-connector pan connection system allows for setout adjustments from 80mm to 185mm with a recommended setout of 140mm providing installation versatility for both new and renovation applications. The cistern is back inlet only with 1/2" B.S.P. inlet stop valve and inlet connection concealed within the cistern. Fitted with low profile chrome plated push buttons and the Unifill inlet valve for ultra quiet fast fill as standard. For an update on Smartflush refer to www.smartinnovation.com.au. The back inlet cistern is fitted with an ultra quiet fast fill inlet valve as standard.

Pan: **Opal II Easy Height** 4.5 litre full flush washdown pan with box flushing rim.
Traps: Universal trap for S or P-trap installations. 50mm vent option available.
Cisterns: **Opal II Smartflush Cistern** – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Standard back inlet.
Vandal Resistant Conversion Kit – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy use commercial areas. Code No.750109.
 Cistern inlet stop valve and inlet connection is concealed within the cistern and is included.

Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.

Fixing: The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.

Seats: The **Opal II Soft Close** toilet seat is provided as standard with the Opal II Easy Height suite. A quality solid section compression moulded toilet seat fitted with buffers and chrome hinges.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

