

caroma®

Profile 5 Deluxe


Vitreous China 4.5/3 litre Dual Flush
Close-Coupled Toilet Suite



CI/SfB	(74.1)	g3
Date	July 2008	

Supersedes all previous issues

3.28.4



Profile 5 Deluxe with Integrated Hand Basin

Vitreous China 4.5/3 litre Dual Flush Close-Coupled Toilet Suite with Integrated Hand Basin (IHB)



A close-coupled suite with smooth round corners and a concealed trap for ease of cleaning, the **Profile 5 Deluxe (IHB)** matched suite uses Caroma Smartflush technology to deliver the latest water-saving technology in sanitaryware products. The **Profile 5 Deluxe (IHB)** close-coupled vitreous china toilet suite delivers a 4.5/3 litre dual flush. The Profile cistern with hand basin lid is an integrated system comprising of cistern with high performance outlet valve, fitted with low profile push buttons. Australia's first 5 star rated toilet suite. An innovative dual-flush push button and spout combination that saves water by allowing the same water to be used for two purposes. Fresh water is first used for hand washing and then flows into cistern to ultimately flush the toilet.

For an update on Smartflush refer to www.smartinnovation.com.au

- Pan:** **Caravelle Smartflush** – 4.5 litre full flush washdown pan with open flushing rim.
- Traps:** S or P-trap unvented only.
- Cisterns:** **Profile Smartflush (IHB)** – has a screw down fitted hand basin lid and is suitable for domestic and light commercial applications.
- Inlet Valve and Overflow:** **Standard Bottom Entry Cistern** – available as right hand inlet which is interchangeable and incorporates new Quietflow 2 inlet valve. Internal overflow only.
Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant.
- Fixing:** The cistern is fixed directly to the pan with a robust base fixing system without the need for wall fixing.
- Seats:** The **Avalon Soft Close** toilet seat is provided as standard with the Profile 5 Deluxe (IHB) toilet suite. See Sheet 5.01 Seats for further details.
- Colours:** White only.
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

