

caroma®

Regal Deluxe


Vitreous China 4.5/3 litre Dual Flush
Close-Coupled Toilet Suite



CI/SfB	(74.1)	g3
Date	July 2008	

Supersedes all previous issues

3.26.2



Regal Deluxe

Vitreous China 4.5/3 litre Dual Flush Close-Coupled Toilet Suite with Seat



A close-coupled 4.5/3 litre dual flush toilet suite featuring a compact cistern design and simple lines with a concealed trap for easy cleaning. The cistern incorporates a dual flush mechanism which has been specially developed with the **Regal Deluxe** toilet suite to ensure optimum flushing performance. Due to the substantial water saving benefits achieved by the 4.5/3 litre dual flush system the matched suite is suitable for multi purpose applications and can be used where authorised for septic installations. The low profile push buttons are easy to operate and have durable moulded symbols to clearly identify the flushing volume.

- Pan:** **Caravelle** 4.5 litre full flush washdown pan with open flushing rim.
- Traps:** S or P-trap unvented only.
- Cisterns:** **Regal 2000 Cistern** – has a free fitting lid and is suitable for domestic and light commercial applications.
Vandal Resistant Conversion Kit – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109.
- Inlet Valve and Overflow:** **Standard Bottom Entry Cistern** – available as right hand inlet which is interchangeable and incorporates new Quietflow 2 inlet valve. Internal overflow only. **Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant.**
- Fixing:** The cistern is fixed directly to the pan with a robust base fixing system without the need for wall fixing.
- Seats:** The **Trident** toilet seat is provided with the Regal Deluxe toilet suite. See Sheet 5.01 Seats for further details.
- Colours:** White only.
- Specifications:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

Setout Range using Optional 40mm offset connector

Regal Deluxe Toilet Suites:	Code
— with Trident Seat	
S-trap	RH inlet 984560
P-trap	RH inlet 984561
Optional 40mm Offset Connector	687270

Note: All height dimensions to underside of pan, make allowance for bedding.

Bedding: The pan should be fixed to the floor with a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast drying cement in the bedding mixture. When bedded the back of the foot of the pan should be approximately 10mm above the finished floor.

Screw fixing: The pan should be bedded with an acetic cured silicone sealant and fixed with corrosion resistant screws and pan guard washers. Use Caroma screw fixing kit. Code No.601150.