

caroma®

| | | |
|--------|-----------|----|
| CI/SfB | (74.2) | g3 |
| Date | July 2008 | |

Supersedes all previous issues

Vintage

Vitreous China Vanity Basin

Nominal Size 540mm x 430mm

Shown with chrome waste (supplied as standard late 2008).

2.04.1



Shown with chrome waste (supplied as standard late 2008).

Vintage

Vitreous China Vanity Basin

Basin Size: 540mm x 430mm (nominal)



A quality traditionally styled elliptical self rimming vanity basin which incorporates authentic design elements from the Australian Federation period featuring two scalloped soap holders and curved splash back. The **Vintage** basin rim is sealed to the counter top with an acetic cured silicone sealant. The 430mm basin projection suits compact vanity tops. The basin has been designed to complement other products in the Vintage range and is ideal for use with the gold or chrome plated Colonial tapware. The basin is suitable for general purpose installations where a traditional style is required.

Tap Holes: The basin is available in: one taphole Code No.653015 and three taphole Code No.653035 options.

Waste Outlet: The basin has been designed for the Caroma Uni-waste outlet suitable for a 40mm trap connection. Coloured plastic flush fitting Uni plug and waste supplied. For applications where a chrome plated brass waste is required there are four suitable Uni-wastes available in the following options — Flush Fitting Plug and Waste Code No.687140, Vandal Resistant Flush Fitting Plug and Waste Code No.687141, Covered Plug and Waste Code No.687142 and Vandal Resistant Covered Plug and Waste Code No.687143.

Bowl Capacity: 4.5 litres to overflow.

Overflow: Overflow available only. Designed for maximum tap flow rate of 15 litres/minute.

Fixing: The underside of the basin rim must be sealed to the counter top with an acetic cured silicone sealant. **Epoxy type glues must not be used.** The basin is supplied with a template which must be used for the counter top cut-out.

Colours: White and Ivory.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

