

# caroma®


CI/SfB	(74.1)	g3
Date	July 2008	

Supersedes all previous issues

## Integra Invisi II Urinal Suite

# 7.03.1

Vitreous China Wall-Hung Boxed Rim  
Urinal with Invisi II Cistern for  
Inwall, Induct or Inceiling applications



Available November 2008

# Integra Invisi II Urinal Suite

## Vitreous China Wall-Hung Boxed Rim Urinal with Invisi II Cistern for Inwall, Induct or Inceiling applications



A wall hung urinal of modern design with concealed integral trap and bracketing to provide a smooth easy to clean outer shroud for low cost maintenance. The box rim flush provides for the wash down of the entire inside area of the bowl on each flush. The grate is vitreous china and factory fitted. Concealed cistern and plumbing fittings provide space saving, ease of cleaning and performance matched components to maximise flushing efficiency.

**Integra Invisi II** urinal suite Code No.743100W.

- Inlet:** Back inlet urinal with concealed sparge pipe and compression rubber fitting.
- Outlet:** Two rubber connection seals are provided for a push on connection with either 50mm on brass tube and 50mm I.D. PVC Waste Pipe tube.
- Flush Action:** Box rim.
- Cistern:** **Invisi II Cistern** – suitable for inwall, induct and inceiling applications. Achieves a 3 star water efficiency rating when installed as a single stall urinal. Buttons are supplied separately, see page 6.15.1 for button and panel options. For inwall applications a blank access panel and remote single flush button are required (not supplied). For induct or inceiling applications where access is available to the cistern and button either the remote or custom buttons are suitable (not supplied).
- Fixing:** **Urinal** is fixed to the wall with the **D.775 Concealed Bracket** Code No.687130. **Cistern** is simply mounted into position by clipping onto the two quick clip mounting brackets which are secured with screws to the studwork or induct brickwork. Cistern brackets supplied.
- Colours:** White only.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

